


LIQUID FERTILIZER CART

Free Form liquid fertilizer carts are available in three popular model sizes and come complete with tank, trailer, tires and a ground drive kit. To suit individual needs, customers have the freedom to source their own pumps and plumbing, or to purchase complete kits from Free Form Plastics.



- ▶ The durable cone bottom tank features a 10° minimal slope angle which delivers complete drainage with a low center of gravity for greater stability on uneven terrain. A unique, field-proven gooseneck style hitch allows the tightest of turns.
- ▶ Standard-equipped with a manual disconnect drive.
- ▶ Pump mounting plates installed for most common pumps.
- ▶ Tanks are rated for liquid up to 20 lb per gallon.
- ▶ Tanks are held in place with adjustable nylon straps (*comes with ratchets for ease of adjustment*)
- ▶ Standard equipped with R1 Traction lug tires.
- ▶ Offset wheel tracking reduces soil compaction.
- ▶ Transport light package - standard.
- ▶ Comes standard with an electric drive clutch.
- ▶ Rear tow hitch - standard.
- ▶ Tank access ladder - standard on LC2000 and LC2500 models only.
- ▶ Optional 540/65R24 front and 30.5L x 32R2 Rice lug rear tire package.



The mechanical ground drive system is “quick detach”, has a spring loaded drive chain tensioner and features an adjustment bolt to allow the drive wheel chain and sprocket to remain tight.



The front end of the Free Form LFC is engineered using the proven design of the Bourgault Air Seeder. This design allows for a full range of motion, along with outstanding durability. The large fifth wheel plate resists wear by utilizing a polymer wear pad. The front axle pivots on a lubricated pin and bushing system which offers rugged, trouble-free operation.



The LC series Liquid Cart frame is common throughout the models. This feature allows the user to upgrade the cart’s capacity by simply changing the tank. The frame design has undergone extensive field and endurance testing to ensure years of trouble-free service.

MODEL	CAPACITY		SPECIFICATIONS			
	IMP. GAL.	U.S. GAL.	LENGTH	WIDTH	HEIGHT	STANDARD FITTING
LC-1500	1500	1800	288"	161"	92"	2" HD
LC-2000	2000	2400	288"	161"	108"	2" HD
LC-2500	2500	3000	288"	161"	124"	2" HD

MODEL	STANDARD TIRE		OPTIONAL TIRE	
	FRONT	REAR	FRONT	REAR
LC-1500	21.5L x 16.1 R1 Traction	23.1 x 26 R1 Traction	21.5L x 16.1 R1 Traction	28L x 26 R1 Traction
LC-2000	21.5L x 16.1 R1 Traction	28L x 26 R1 Traction	540/65 R24 R1W Traction	30.5L x 32 R2 Rice Lug
LC-2500	21.5L x 16.1 R1 Traction	28L x 26 R1 Traction	540/65 R24 R1W Traction	30.5L x 32 R2 Rice Lug

Cart pricing includes tires, excluding 540/65 R24 and 30.5L x 32 R2 Rice Lug