

PORTABLE LIQUID STORAGE



Free Form designed the PLS to meet increasing demands for on-site liquid storage. The PLS is available in a variety of sizes ranging from 4000 imp. (4800 U.S.) gallons to 7400 imp. (8880 U.S.) gallons. This unit was designed with ease of operation in mind. A self-contained hydraulic system is standard to allow simple conversion from road to field and back. The tanks are heavy-duty 10° cone bottom to allow for complete drainage of product and meet the demanding conditions of our customers. The PLS is suitable for storage of a wide array of liquids including liquid fertilizer, liquid feed supplement, herbicide and water for livestock or spraying operations. Whatever your needs, the PLS meets the increasing demands for on-site liquid storage.



PORTABLE LIQUID STORAGE

SPECIFICATIONS

MODEL	TANK COLOUR	CAPACITY IMP/US	LENGTH	WIDTH	HEIGHT	PART #
PLS-7400	Trans White	7400/8880	260"	104"	162"	1337
PLS-7400	Black	7400/8880	260"	104"	162"	26006-39
PLS-5000	Trans White	5000/6000	260"	104"	122"	1642
PLS-5000	Black	5000/6000	260"	104"	122"	26006-52
PLS-4000	Trans White	4000/4800	260"	104"	106"	Call
PLS-4000	Black	4000/4800	260"	104"	106"	Call

* Field Ready units above come with Transport Light Package and 3" Banjo plumbing Package

OPTIONS

6.5 HP Honda c/w Banjo Wetseal Pump, recirc plumbing	26006-40
13 HP Honda Elec Start c/w Banjo Wetseal Pump, recirc plumbing	26006-41
Pintle Hitch	1641
2-5/16" Ball Socket Hitch	26004-47

Features

- Largest unit will hold an entire B-train load of Liquid fertilizer.
- Tanks are rated for liquid up to 20 lbs. per gallon.
- Tanks have an optimum 10° cone bottom for complete drainage.
- Minimal trailer tongue weight allows unit to be easily towed by a variety of vehicles.
- Single load and unload port with remote access to valves on both tanks.
- Completely plumbed with Banjo Fittings for years of trouble free service.
- Shield to protect main valve from damage due to road debris.
- Both tanks are conveniently connected to the front of the unit where central loading and unloading can be done.
- Heavy-duty fittings and valves are used throughout the unit making it very durable.
- Camlock connections are standard on all hose ends to allow removal of hoses for clean out.
(3" plumbing is standard with optional 2" available upon request.)



- An adjustable double clevis hitch is standard on all models. Optional hitch choices include a pintle, or a 2-5/16" socket.



- Added safety features include: a double safety chain, a light package, a slow moving sign, and side clearance reflectors. Tires are DOT rated for highway use.



- Ball valves are located at the bottom of both tanks to allow complete control of the fluid and to help prevent the possibility of lost product. The valves are operated with ease using remote access handles located on the side of the unit. These handles are lockable to prevent vandalism or theft of the product.



- Self containing hydraulic system for lifting and lowering unit. Tires are rated for highway speed. (11L x 15" DOT GOOD YEAR FARM AND HIGHWAY SERVICE)



- Each tank is secured with three (3) custom-made straps. The straps are bolted to the lifting lugs on the top of the tank with 1/2" bolts and secured to the cone with ratcheting buckles. The ratcheting buckles allow for easy, and necessary adjustment to the strap tension, compensating for changing dimensions caused by temperature variations.



- Optional Honda Pumps
6.5 HP Honda c/w Banjo Wetseal Pump, recirc plumbing
13 HP Honda Elec Start c/w Banjo Wetseal Pump, recirc plumbing